TECHNOLOGY DEVELOPMENT DATA SHEET



Waste Inspection Tomography (WIT)



Developer: Bio-Imaging Research, Inc. Contract Number: DE-AC21-93MC30173

Crosscutting Area: CMST

Problem:

Characterization of the contents of nuclear waste drums is required for disposition decisions, safe transportation, and permanent storage. Movement of waste drums on and off storage sites is regulated for safety and environmental Examination of drum reasons. contents with invasive techniques is expensive because of the safety precautions necessary when handling nuclear waste. Currently used nondestructive techniques such as real time radiography (RTR) lack the capability to identify regulated contents such as free-liquid volume. Thus, characterization of nuclear waste is logistically difficult, expensive, and generally does not provide quantitative results.

Solution:

A mobile waste inspection tomography (WIT) system that can be brought to the waste site to perform tomographic characterization of nuclear waste drums using a multimodality approach. In the WIT system, highenergy computed tomography (CT), emission tomography (ECT) and spectroscopy emission nondestructive assay (NDA) are integrated on a mobile trailer. WIT


and produces quantitative results. WIT will safely and cost-effectively identify contents, provide two- and three-dimensional information about contents, locate isotope emissions, and identify the emitting isotope species.

is nondestructive and noninvasive,

- ▶3-D, readily interpreted, near realtime images of drum contents facilitates evaluation, processing, and disposition of drums.
- ► Archived data and content images support engineering decisions and regulatory compliance.

Technology:

Benefits:



Mixed Waste

- ▶Rapid characterization of 55-110 gallon drums for radioactive and heavy-metal content and location, wall thickness, and free-liquid volume and location.
- ▶Effective for low-level, transuranic, and mixed wastes in a variety of matrices including cement, glass, polymers, combustibles, loose soil, heterogeneous metals, and supercompacted materials.
- ► Mobile system optimizes logistics.

The WIT design provides the following imaging capabilities in a mobile system with reasonable throughput and cost. nondestructively quantifies regulated parameters. This includes of drum-wall measurements thickness and free-liquid volume, and identification of heavy-metal densities. CT also identifies drum contents through 2-D and 3-D imaging. ECT can locate emissions within a drum, identifying a point source, a locus of points, or a uniform distribution of emissions.



May 1999



NDA identifies the emitting isotopic species. The WIT system has the capability to characterize containers up to 42 inches high by 32 inches wide.

The following are important features of the WIT system:

- Mobile Trailer: Includes a 48-foot long air-ride trailer with control equipment, scanner rooms, radiation shielding and safety interlocks, intercom and closed circuit TV, HVAC, an electrical generator with alternate connection to a local power source, and fire suppression and security systems.
- Drum Handling: Loading and unloading will be accomplished using site-supplied forklift trucks. Overpack protection for older or breached drums is required.
- ►CT: A 2 MeV CT scanner with digital radiography capability, including motion control for drum manipulation during scanning and high-speed data collection for volume imaging.
- ►ECT: Gamma cameras provide for emission volume imaging to locate emission sources within the drum.
- Spectroscopic Assay: Energysensitive NDA reveals the emission

spectrum, identifying the emitting isotopic species. Capability for active and passive CT is also provided to allow validation of the system. Lawrence Livermore National Laboratory is developing this technology application under a separate agreement.

- ► Volume Display: A volume image processor and display provides CT and ECT data fusion to identify the source of the radioactive emission.
- Archive Storage: Optical disk storage of digitized images and raw data, as well as VCR recording of operator review protocols, are provided.

Contacts:

Bio-Imaging Research Inc. is an industrial CT manufacturer and the WIT contractor for the Department of Energy (DOE). For information on this project, the contractor contact is:

Principal Investigator: Mr. Richard T. Bernardi Bio-Imaging Research, Inc. 425 Barclay Boulevard Lincolnshire, IL 60069 Phone: (847) 634-6425 Fax: (847) 634-6440


E-mail: None

DOE's Federal Energy Technology Center supports the Environmental Management - Office of Science and Technology by contracting the research and development of new technologies for waste site characterization and cleanup. For information regarding this project, the DOE contact is:

DOE Project Manager: Mr. P. Steven Cooke Federal Energy Technology Center 3610 Collins Ferry Road P.O. Box 880 Morgantown, WV 26507-0880

Phone: (304) 285-5437 Fax: (304) 285-4403

E-mail: pcooke@fetc.doe.gov



6

